

## AGRIMAX RT 955 - Spécifications techniques



### Description

AGRIMAX RT 955 est un pneu radial BKT idéal pour les applications cultures en couloir, et certaines tailles conviennent même pour la pulvérisation et les vignes. Avec son épaulement arrondi, la bande de roulement assure d'excellentes performances en matière de traction, stabilité et qualités d'autonettoyage. Grâce à sa carcasse robuste, AGRIMAX RT 955 garantit une capacité de charge élevée.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Pulvérisateur • Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	230/95 R 36 (9.5 R 36)
LI/SS	130 A8/B

## Dimensions US Standard

Usa code	94027477
Section Width (inch)	9.4
Overall Diameter (inch)	53.2
Static Loaded Radius (inch)	25.2
Rolling Circumference (inch)	161.9
Rim Rec	W 8
Rim Alt	W 7
ECE	E4-106R-000765
TRA Code	R1

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	1640	2140	2600	2850	3020	3320	3600	3900	4180	-
25	1640	2140	2600	2850	3020	3320	3600	3900	4180	-
20	1750	2290	2790	3050	3240	3550	3870	4180	4490	-
5	1950	2460	3020	3580	4160	4280	4780	5280	5790	6280

Printed on 03/12/2023 06:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..