

AGRIMAX RT 955 - Spécifications techniques



Description

AGRIMAX RT 955 est un pneu radial BKT idéal pour les applications cultures en couloir, et certaines tailles conviennent même pour la pulvérisation et les vignes. Avec son épaulement arrondi, la bande de roulement assure d'excellentes performances en matière de traction, stabilité et qualités d'autonettoyage. Grâce à sa carcasse robuste, AGRIMAX RT 955 garantit une capacité de charge élevée.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur • Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	230/95 R 42 (9.5 R 42)
LI/SS	133 A8/B

Dimensions International Standard

Section Width (mm)	238
Overall Diameter (mm)	1506
Static Loaded Radius (mm)	714
Rolling Circumference (mm)	4595
SRI (mm)	725
Rim Rec	W 8
Rim Alt	W 7
ECE	E4-106R-000772
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	805	1055	1280	1405	1485	1630	1775	1920	2060	-
40	805	1055	1280	1405	1485	1630	1775	1920	2060	-
30	860	1125	1370	1500	1590	1745	1900	2055	2205	-
10	960	1210	1485	1765	2040	2105	2350	2600	2845	3090

Printed on 08/12/2023 07:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..