

AGRIMAX RT 955 - Spécifications techniques



Description

AGRIMAX RT 955 est un pneu radial BKT idéal pour les applications cultures en couloir, et certaines tailles conviennent même pour la pulvérisation et les vignes. Avec son épaulement arrondi, la bande de roulement assure d'excellentes performances en matière de traction, stabilité et qualités d'autonettoyage. Grâce à sa carcasse robuste, AGRIMAX RT 955 garantit une capacité de charge élevée.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur • Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	270/80 R 36
LI/SS	134 A8/B

Dimensions International Standard

Section Width (mm)	275
Overall Diameter (mm)	1346
Static Loaded Radius (mm)	629
Rolling Circumference (mm)	4090
SRI (mm)	650
Rim Rec	W9
Rim Alt	W8; W10
ECE	E11-106R-006758
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
50	745	870	1000	1125	1255	1360	1510	1590	1740	1890	2015	2120
40	745	870	1000	1125	1255	1360	1510	1590	1740	1890	2015	2120
30	795	935	1070	1205	1340	1455	1615	1705	1865	2025	2160	2270
10	1115	1305	1495	1690	1880	2040	2260	2385	2610	2835	3025	3180

Printed on 06/12/2023 03:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..