

AGRIMAX RT 955 - Spécifications techniques



Description

AGRIMAX RT 955 est un pneu radial BKT idéal pour les applications cultures en couloir, et certaines tailles conviennent même pour la pulvérisation et les vignes. Avec son épaulement arrondi, la bande de roulement assure d'excellentes performances en matière de traction, stabilité et qualités d'autonettoyage. Grâce à sa carcasse robuste, AGRIMAX RT 955 garantit une capacité de charge élevée.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur • Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	340/85 R 48 (13.6 R 48)
LI/SS	152 A8/B

Dimensions International Standard

Section Width (mm)	353
Overall Diameter (mm)	1797
Static Loaded Radius (mm)	855
Rolling Circumference (mm)	5572
SRI (mm)	875
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-000800
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1385	1815	2205	2415	2560	2805	3055	3305	3550	-
40	1385	1815	2205	2415	2560	2805	3055	3305	3550	-
30	1485	1940	2360	2585	2740	3005	3270	3535	3800	-
10	1655	2080	2560	3040	3515	3625	4050	4475	4900	5325

Printed on 09/12/2023 15:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..