

AGRIMAX RT 955 - Spécifications techniques



Description

AGRIMAX RT 955 est un pneu radial BKT idéal pour les applications cultures en couloir, et certaines tailles conviennent même pour la pulvérisation et les vignes. Avec son épaulement arrondi, la bande de roulement assure d'excellentes performances en matière de traction, stabilité et qualités d'autonettoyage. Grâce à sa carcasse robuste, AGRIMAX RT 955 garantit une capacité de charge élevée.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur • Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	340/85 R 48 (13.6 R 48)
LI/SS	152 A8/B

Dimensions US Standard

Usa code	94029426
Section Width (inch)	13.9
Overall Diameter (inch)	70.7
Static Loaded Radius (inch)	33.7
Rolling Circumference (inch)	219.4
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-000800
TRA Code	R1

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	3050	4000	4860	5320	5640	6180	6730	7290	7830	-
25	3050	4000	4860	5320	5640	6180	6730	7290	7830	-
20	3270	4280	5200	5700	6040	6620	7210	7790	8380	-
5	3650	4590	5640	6700	7750	7990	8930	9870	10800	11740

Printed on 03/12/2023 05:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..