

AGRIMAX SPARGO - Spécifications techniques



Description

AGRIMAX SPARGO est le pneu BKT spécial pour les applications en couloirs, conçu pour améliorer la productivité du champ en préservant le sol à long terme. Il a d'excellentes propriétés d'auto-nettoyage et une capacité de charge supérieure à des pressions standard. AGRIMAX SPARGO garantit une excellente traction en même temps qu'une grande stabilité aux champs et lors des déplacements sur la route.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur

Version	STANDARD
Type	TL
Tyre Size	VF 480/80 R 46
LI/SS	177 D

Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1936
Static Loaded Radius (mm)	892
Rolling Circumference (mm)	5907
SRI (mm)	925
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E11-106R-004756
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6
70	3715	4115	4515	4710	4980	5110	5245	5510	5775	5975	6240	6440	6640
From 65 to 40	4085	4525	4960	5180	5475	5620	5765	6055	6350	6570	6860	7080	7300
30	4165	4615	5060	5285	5580	5730	5880	6175	6475	6700	6995	7220	7445
20	4250	4705	5160	5385	5690	5840	5995	6295	6600	6830	7130	7360	7590
10	4495	4975	5460	5700	6020	6180	6340	6660	6985	7225	7545	7785	8030

Printed on 23/02/2024 14:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..