

AIROMAX AM 27 - Fiche de données



Description

AIROMAX AM 27 est un pneu pour une utilisation essentiellement sur route, idéal pour les applications sur grues dans le secteur bâtiment. Le pneu se distingue de par sa résistance à la chaleur et son confort exceptionnel. AIROMAX AM 27 est un pneu à haute vitesse particulièrement adapté pour toutes les opérations qui demandent un niveau de manœuvrabilité élevé.

UM

International Standard

Construction

 RADIAL

Machinery

Industriel: Grue automotrice

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
385/95 R 24 (14.00 R 24)	STANDARD	170 F	10.00W		372	1363	626	4175	TT	E11-54R-0015910
385/95 R 25 (14.00 R 25)	STANDARD	170 F	10.00/1.5		372	1363	626	4175	TL	E11-54R-0015911
445/95 R 25 (16.00 R 25)	STANDARD	174 F	11.25/2.0	11.00/1.7 CR ; 11.00/1.7CRL	440	1490	695	4587	TL	E4-54R-0028867
505/95 R 25 (18.00 R 25)	STANDARD	186 E	13.00/2.5		492	1600	728	4900	TL	
525/80 R 25 (20.5 R 25)	STANDARD	176 F	17.00/2.0	17.00/1.7 CR	530	1481	681	4534	TL	E11-54R-0016681

Printed on 20/02/2024 23:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..