

AIROMAX AM 543 - Spécifications techniques



Description

AIROMAX AM 543 est le pneu idéal pour les applications avec grues dans le secteur bâtiment. Ce pneu fait preuve d'une excellente traction associée à une grande stabilité. Du fait que les pneus pour grues sont soumis à des sollicitations et à des conditions d'utilisation extrêmes, AIROMAX AM 543 a été conçu pour fournir une excellente résistance à la chaleur. De plus il convient pour toutes les opérations qui demandent un niveau de manœuvrabilité élevé.

UM

International Standard

Construction

 RADIAL

Machinery

Industriel: Grue automotrice

Version	STANDARD
Type	TL
Tyre Size	445/95 R 25 (16.00 R 25)
LI/SS	177 E

Dimensions International Standard

Overall Width (mm)	435
Overall Diameter (mm)	1480
Static Loaded Radius (mm)	670
Rolling Circumference (mm)	4502
Rim Rec	11.25/2.0
Rim Alt	11.00/1.7 CR ; 11.00/1.7CRL

Load capacity (Kg)

km/h / bar	9.00
30	9500
40	9000
50	8500
60	8175
70	7300
80	6000
90	5150
100	4375

Printed on 25/04/2024 15:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..