

ARROW - Spécifications techniques



Description

ARROW convient pour toutes les applications de transport avec remorques. Ce pneu a été conçu pour une utilisation essentiellement sur route et assure un kilométrage supérieur et un cycle de vie plus long. ARROW offre une capacité de charge élevée même à grande vitesse.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Remorque

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 6.50 - 14 |

Dimensions International Standard

| | |
|------------------------------|----------------|
| Ply Rating | 10 |
| Section Width (mm) | 175 |
| Overall Diameter (mm) | 695 |
| Rim Rec | 4.5 J |
| ECE | E4-54R-0024093 |

Load capacity (Kg)

| | | |
|--|------------|------|
| | km/h / bar | 5.00 |
| | 100 LS | 925 |
| | 100 LD | 815 |

Printed on 20/04/2024 07:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..