

## AS 2001 - Spécifications techniques



### Description

AS 2001 est un pneu diagonal à couches croisées, parfaitement adapté pour les tracteurs dans les opérations de travail de la terre et de transport. Le dessin particulier assure une excellente traction et des propriétés élevées d'auto-nettoyage. AS 2001 a été réalisé avec un mélange résistant à tous les types de coupure qui confère aussi une grande capacité de charge.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	16.9 - 28
LI/SS	135 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	429
Overall Diameter (mm)	1420
Static Loaded Radius (mm)	651
Rolling Circumference (mm)	4319
SRI (mm)	675
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-003508
TRA Code	R1

## Load capacity (Kg)

km/h / bar	1.70
30	2180

Printed on 25/04/2024 19:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..