

## AS 505 - Spécifications techniques



### Description

AS 505 est parfaitement adapté pour le travail de la terre avec des remorques et des outils agricoles. Ce pneu se distingue de par ses excellentes propriétés d'auto-nettoyage et par une traction supérieure sur le terrain, notamment sur les sols boueux. Le pneu assure aussi un long cycle de vie.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Outillage agricole • Remorque

Version	STANDARD
Type	TL
Tyre Size	6.5/80 - 15
LI/SS DRIVE WHEEL	86 A8
LI/SS FREE ROLLING	98 A8

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	171
Overall Diameter (mm)	695
Static Loaded Radius (mm)	325
Rolling Circumference (mm)	2106
Rim Rec	5.0
Rim Alt	4½ K ; 5 K ; 5 J
ECE	E4-106R-002188

## Load capacity (Kg)

	km/h / bar	3.60
	10 FR	1050
	25 FR	895
	30 FR	840
	40 FR	750
	10 DW	740
	25 DW	630
	30 DW	595
	40 DW	530

Printed on 24/04/2024 21:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..