

## AS 511 - Spécifications techniques



### Description

AS 511 est parfaitement adapté pour les outils agricoles dans les applications sur pelouses. La carcasse robuste et le mélange de la bande de roulement particulièrement résistant aux coupures et déchirures assurent une stabilité exceptionnelle et des performances accrues. Grâce à la large zone de contact, AS 511 fournit une excellente traction et minimise le compactage du sol.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Outillage agricole

Version	STANDARD
Type	TL
Tyre Size	31 X 15.50 R 15
LI/SS	122 B

## Dimensions International Standard

Section Width (mm)	388
Overall Diameter (mm)	785
Static Loaded Radius (mm)	353
Rolling Circumference (mm)	2387
Rim Rec	13 LB
ECE	E11-106R-005098

## Load capacity (Kg)

km/h / bar	2.8
50	1500

Printed on 01/04/2023 16:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..