

AT 111 HD - Spécifications techniques



Description

AT 111 HD convient pour les applications sportives Tout Terrain avec les véhicules ATV/VTT. La profondeur augmentée et la forte épaisseur des flancs offrent une adhérence et une capacité de freinage remarquables ainsi qu'une traction et un contrôle exceptionnels lors des manœuvres de survirage à grande vitesse. AT 111 HD se distingue de par un long cycle de vie.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Véhicule ATV

Version	STANDARD
Type	TL
Tyre Size	AT 22 X 7 - 10

Dimensions US Standard

Usa code	94027033
Ply Rating	6
Section Width (inch)	6.9
Overall Diameter (inch)	22
Rim Rec	5.5 AT
Rim Alt	6.0 AT
ECE	E4-75R-0006331

Load capacity (lbs)

mph / psi	7
62	255

Printed on 14/04/2024 04:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..