

AT 111 HD - Spécifications techniques



Description

AT 111 HD convient pour les applications sportives Tout Terrain avec les véhicules ATV/VTT. La profondeur augmentée et la forte épaisseur des flancs offrent une adhérence et une capacité de freinage remarquables ainsi qu'une traction et un contrôle exceptionnels lors des manœuvres de survirage à grande vitesse. AT 111 HD se distingue de par un long cycle de vie.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Véhicule ATV

Version	STANDARD
Type	TL
Tyre Size	AT 23 X 7 - 10

Dimensions International Standard

Ply Rating	6
Section Width (mm)	174
Overall Diameter (mm)	585
Rim Rec	5.5 AT
Rim Alt	6.0 AT
ECE	E4-75R-0006335

Load capacity (Kg)

km/h / bar	0.45
100	125

Printed on 26/04/2024 21:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..