

AT 171 - Spécifications techniques



Description

AT 171 a été conçu pour les tracteurs pour les cours 4x4 dans la boue. Le dessin directionnel particulier extra-profond de la bande de roulement assure une excellente traction sur les surfaces mouillées et boueuses.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Véhicule ATV • Véhicule pour les course dans la bone

Version	STANDARD
Type	TL
Tyre Size	AT 35 X 9 - 20
LI/SS	85 A8 / 61 F

Dimensions US Standard

Usa code	94055173
Ply Rating	6
Section Width (inch)	7.9
Overall Diameter (inch)	35.2
Static Loaded Radius (inch)	16.5
Rolling Circumference (inch)	105.1
Rim Rec	W 7
Rim Alt	W 6
TRA Code	R1W+

Load capacity (lbs)

mph / psi	20	15
25 MUD BOGGING	1135	-
50 MUD BOGGING	567	-
25 CASUAL TRANSPORT	-	940
50 CASUL TRANSPORT	-	481

Printed on 19/04/2024 02:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..