

AT 316 - Spécifications techniques



Description

AT 316 est adapté pour les tracteurs utilitaires compacts des services municipaux de voirie. Le dessin particulier de la bande de roulement assure une excellente traction sans compromettre la protection du champ – ce qui est essentiel pour ce type d'application. Le pneu AT 316 est aussi disponible en version "aramid belted", avec des ceintures en aramide qui permettent une meilleure résistance aux perforations.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur compact

Version	ARAMID BELTED
Type	TL
Tyre Size	24 X 12.00 - 12

Dimensions International Standard

Ply Rating	6
Section Width (mm)	315
Overall Diameter (mm)	610
Static Loaded Radius (mm)	271
Rolling Circumference (mm)	1769
Rim Rec	10.50 I - 55 ; I - 70 ; I - 90

Load capacity (Kg)

km/h / bar	2.20
15	1030

Printed on 25/04/2024 18:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..