

## AT 603 - Spécifications techniques



### Description

AT 603 est un pneu agro-industriel pour les outils agricoles et les chargeuses-pelleteuses. AT 603 a été conçu pour assurer une durabilité supérieure et une excellente traction sur la roue motrice et donc de très bonnes performances sur toutes les surfaces même que des qualités d'autonettoyage extraordinaires. Le pneu AT 603 est disponible en version "spécial" avec une carcasse renforcée, tandis que en la version "HD" qui offre une meilleure résistance aux coupures et déchirures.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Chargeuse-pelleteuse • Outillage agricole  
Industriel: Chargeuse-pelleteuse

Version	HD
Type	TL
Tyre Size	10.5/80 - 18
LI/SS DRIVE WHEEL	119 A8
LI/SS FREE ROLLING	131 A8

## Dimensions US Standard

Usa code	94032570
Ply Rating	10
Section Width (inch)	10.8
Overall Diameter (inch)	35.7
Static Loaded Radius (inch)	16.6
Rolling Circumference (inch)	107.4
Rim Rec	W 9
Rim Alt	W 8 ; 9
ECE	E11-106R-004546

## Load capacity (lbs)

mph / psi	54
5 FR	6020
15 FR	5110
20 FR	4820
25 FR	4300
5 DW	4200
15 DW	3570
20 DW	3360
25 DW	3000

Printed on 26/04/2024 19:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..