

AT 603 - Spécifications techniques



Description

AT 603 est un pneu agro-industriel pour les outils agricoles et les chargeuses-pelleteuses. AT 603 a été conçu pour assurer une durabilité supérieure et une excellente traction sur la roue motrice et donc de très bonnes performances sur toutes les surfaces même que des qualités d'autonettoyage extraordinaires. Le pneu AT 603 est disponible en version "spécial" avec une carcasse renforcée, tandis que en la version "HD" qui offre une meilleure résistance aux coupures et déchirures.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Chargeuse-pelleteuse • Outillage agricole
Industriel: Chargeuse-pelleteuse

| | |
|--------------------|--------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 12.5/80 - 18 |
| LI/SS DRIVE WHEEL | 129 A8 |
| LI/SS FREE ROLLING | 142 A8 |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94019595 |
| Ply Rating | 12 |
| Section Width (inch) | 12.1 |
| Overall Diameter (inch) | 39.4 |
| Static Loaded Radius (inch) | 17.6 |
| Rolling Circumference (inch) | 119.2 |
| Rim Rec | W 9 |
| Rim Alt | 11 |

Load capacity (lbs)

| mph / psi | 54 |
|-----------|------|
| 5 FR | 8180 |
| 15 FR | 6960 |
| 20 FR | 6550 |
| 25 FR | 5840 |
| 5 DW | 5710 |
| 15 DW | 4850 |
| 20 DW | 4560 |
| 25 DW | 4080 |

Printed on 26/04/2024 22:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..