

AT 625 - Spécifications techniques



Description

AT 625 est adapté pour les chargeuses-pelleteuses et chargeuses compactes dans toutes les opérations d'excavation et chargement dans le milieu agricole. La bande de roulement extra profonde garantit une meilleure résistance aux perforations et une durabilité plus élevée. AT 625 offre d'excellentes traction et stabilité ainsi qu'une meilleure résistance aux coupures et déchirures.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Chargeuse-pelleteuse • Chargeuse compacte

Version	INDUSTRIAL
Type	TT
Tyre Size	16.9 - 28
LI/SS	152 A8

Dimensions US Standard

Usa code	94040315
Ply Rating	12
Section Width (inch)	17.7
Overall Diameter (inch)	55.7
Static Loaded Radius (inch)	25.4
Rolling Circumference (inch)	167.5
Rim Rec	DW 15 L
Rim Alt	DW 14 L
TRA Code	R4

Load capacity (lbs)

mph / psi	38
25	7850

Printed on 23/04/2024 17:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..