

AW 09 - Spécifications techniques



Description

AW 09 a été conçu pour le labour du sol, la récolte de foin et les applications de transport avec des outils agricoles, les presses à paille et remorques. Il convient pour être utilisé dans l'agriculture moderne tant sur route que hors route. La carcasse renforcée garantit une capacité de charge élevée et une vie opérationnelle plus longue. AW 09 a été conçu avec un mélange particulièrement résistant aux coupures et déchirures en offrant une résistance excellente aux chaumes.

UM

US Standard

Construction

❖ BIAS

Machinery

Agriculture: Presse à paille • Moissonneuse • Outillage agricole • Remorque

| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 300/80 - 15.3 |
| LI/SS DRIVE WHEEL | 129 A8 |
| LI/SS FREE ROLLING | 141 A8 |

Dimensions US Standard

| | |
|------------------------------|----------------|
| Usa code | 94037803 |
| Section Width (inch) | 11.6 |
| Overall Diameter (inch) | 33.9 |
| Static Loaded Radius (inch) | 14.8 |
| Rolling Circumference (inch) | 99.2 |
| Rim Rec | 9.00 |
| ECE | E4-106R-000376 |

Load capacity (lbs)

| mph / psi | 58 |
|-----------|------|
| 5 FR | 7950 |
| 15 FR | 6760 |
| 20 FR | 6360 |
| 25 FR | 5680 |
| 5 DW | 5710 |
| 15 DW | 4850 |
| 20 DW | 4560 |
| 25 DW | 4080 |

Printed on 26/04/2024 21:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..