

## AW-18 - Spécifications techniques



### Description

AW-18 a été conçu pour les remorques et les machines qui sont utilisées dans les opérations de travail du sol. Sa forme spéciale, avec des pattes non directionnelles et une zone d'épaulement arrondie, permet de ne pas endommager les cultures lors des manœuvres. Le profil de la bande de roulement a été spécialement conçu pour garantir des propriétés autonettoyantes exceptionnelles. AW-18 est également synonyme de confort optimal de pilotage et de réduction de la consommation de carburant.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Agriculture: Outillage agricole

Version	STANDARD
Type	TL
Tyre Size	11.5/80 - 15.3 (300/80 - 15.3)
LI/SS FREE ROLLING	139 A8

## Dimensions US Standard

Usa code	94064045
Section Width (inch)	11.7
Overall Diameter (inch)	33.3
Rim Rec	9.00
ECE	E11-106R-006020

## Load capacity (lbs)

mph / psi	69
5 FR	7500
15 FR	6380
20 FR	6000
25 FR	5360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08/12/2024 05:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..