

## AW 705 - Spécifications techniques



### Description

AW 705 a été conçu pour les outils agricoles et remorques dans les applications de travail de la terre et de transport. Il convient pour être utilisé dans l'agriculture moderne grâce à une durabilité supérieure et une capacité de charge élevée.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Presse à paille • Outillage agricole • Remorque

Version	STANDARD
Type	TL
Tyre Size	15.0/70 - 18
LI/SS FREE ROLLING	151 A8

## Dimensions International Standard

<b>Ply Rating</b>	16
<b>Section Width (mm)</b>	405
<b>Overall Diameter (mm)</b>	1010
<b>Static Loaded Radius (mm)</b>	447
<b>Rolling Circumference (mm)</b>	3092
<b>Rim Rec</b>	13.00
<b>Rim Alt</b>	13 ; W 13
<b>ECE</b>	E4-106R-002266

## Load capacity (Kg)

	km/h / bar	4.25
	10 FR	4830
	25 FR	4105
	30 FR	3865
	40 FR	3450

Printed on 20/04/2024 09:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..