

## AW 705 - Spécifications techniques



### Description

AW 705 a été conçu pour les outils agricoles et remorques dans les applications de travail de la terre et de transport. Il convient pour être utilisé dans l'agriculture moderne grâce à une durabilité supérieure et une capacité de charge élevée.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Presse à paille • Outillage agricole • Remorque

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	400/55 - 22.5
LI/SS FREE ROLLING	156 A8

## Dimensions US Standard

Usa code	94060306
Ply Rating	20
Section Width (inch)	15.9
Overall Diameter (inch)	40
Static Loaded Radius (inch)	17.4
Rolling Circumference (inch)	120.9
Rim Rec	AG 11.75
Rim Alt	12.25 ; AG 13.00

## Load capacity (lbs)

mph / psi	73
5 FR	12345
15 FR	10495
20 FR	9875
25 FR	8820

Printed on 26/04/2024 20:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..