

AW 708 - Spécifications techniques



Description

AW 708 a été conçu pour le travail de la terre et les applications de transport et récolte du foin avec les outils agricoles, remorques et presses à paille. Une version « HD » est disponible avec un mélange particulièrement résistant aux coupures et déchirures.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Outillage agricole • Remorque
Industriel: Remorque

Version	STANDARD
Type	TT
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	145 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	405
Overall Diameter (mm)	875
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2564
Rim Rec	AG 13.00
ECE	E4-106R-002712

Load capacity (Kg)

	km/h / bar	3.60
	10 FR	4060
	25 FR	3450
	30 FR	3250
	40 FR	2900

Printed on 25/04/2024 21:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..