

AW 708 - Fiche de données

Description

AW 708 a été conçu pour le travail de la terre et les applications de transport et récolte du foin avec les outils agricoles, remorques et presses à paille. Une version « HD » est disponible avec un mélange particulièrement résistant aux coupures et déchirures.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Outillage agricole • Remorque
Industriel: Remorque



| SIZE | Version | LI/SS FREE ROLLING | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|---------------|-------------------|--------------------|----|----------|---------|-----|------|-----|------|------|-----------------|
| 400/60 - 15.5 | HD | 149 A8 | 18 | AG 13.00 | | 405 | 875 | 380 | 2564 | TL | E11-106R-004253 |
| 400/60 - 15.5 | SPECIAL | 149 A8 | 18 | AG 13.00 | | 405 | 875 | 380 | 2564 | TT | E11-106R-004255 |
| 400/60 - 15.5 | SPECIAL | 149 A8 | 18 | AG 13.00 | | 405 | 875 | 380 | 2564 | TL | |
| 400/60 - 15.5 | STANDARD | 149 A8 | 18 | AG 13.00 | | 405 | 875 | 380 | 2564 | TL | E4-106R-001543 |
| 400/60 - 15.5 | STANDARD | 136 A8 | 10 | AG 13.00 | | 405 | 875 | 380 | 2564 | TL | E11-106R-003514 |
| 400/60 - 15.5 | STANDARD | 145 A8 | 14 | AG 13.00 | | 405 | 875 | 380 | 2564 | TT | E4-106R-002712 |
| 400/60 - 15.5 | STANDARD | 145 A8 | 14 | AG 13.00 | | 405 | 875 | 380 | 2564 | TL | E4-106R-002712 |
| 400/60 - 15.5 | STUBBLE RESISTANT | 149 A8 | 18 | AG 13.00 | | 405 | 875 | 380 | 2564 | TL | |
| 19.0/45 - 17 | STANDARD | 138 A8 | 10 | 16.00 | | 470 | 866 | 380 | 2536 | TL | E4-106R-002334 |
| 19.0/45 - 17 | STANDARD | 144 A8 | 14 | 16.00 | | 470 | 866 | 380 | 2536 | TL | E4-106R-001883 |
| 19.0/45 - 17 | STANDARD | 148 A8 | 18 | 16.00 | | 470 | 866 | 380 | 2536 | TL | E4-106R-002268 |
| 19.0/45 - 17 | STUBBLE RESISTANT | 152 A8 | 22 | 16.00 | | 470 | 866 | 380 | 2536 | TL | E11-106R-003636 |
| 500/50 - 17 | STANDARD | 140 A8 | 10 | 16.00 | | 500 | 945 | 416 | 2750 | TL | E4-106R-001884 |
| 500/50 - 17 | STANDARD | 149 A8 | 14 | 16.00 | | 500 | 945 | 416 | 2750 | TL | E4-106R-001813 |
| 500/50 - 17 | STANDARD | 152 A8 | 16 | 16.00 | | 500 | 945 | 416 | 2750 | TL | |
| 500/50 - 17 | STANDARD | 154 A8 | 18 | 16.00 | | 500 | 945 | 416 | 2750 | TL | E4-106R-002269 |
| 500/65 - 17 | STANDARD | 160 A8 | 18 | 16.0 | | 525 | 1080 | 462 | 3135 | TL | E11-106R-004549 |
| 520/50 - 17 | STANDARD | 162 A8 | | 16.00 | | 516 | 952 | 404 | 2777 | TL | E11-106R-005852 |

Printed on 26/04/2024 10:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..