

AW 711 - Spécifications techniques



Description

AW 711 est un pneu radial pour les outils agricoles, spécialement conçu pour être utilisé dans l'agriculture moderne et convenant pour des applications de transport, le récolte du foin e le travail de la terre. Grâce au mélange spécial de la bande de roulement, AW 711 assure une longue durée de vie du produit, qu'il soit utilisé sur des surfaces souples ou dures. La faible résistance au roulement pendant le transfert sur route permet de réaliser d'importantes économies quant à la consommation de carburant. Grâce à la technologie VF, AW 711 garantit une capacité de charge élevée à de basses pressions.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Moissonneuse • Outillage agricole

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	340/60 R 16.5
LI/SS	145 A8/B

Dimensions International Standard

Section Width (mm)	324
Overall Diameter (mm)	820
Static Loaded Radius (mm)	368
Rolling Circumference (mm)	2476
SRI (mm)	390
Rim Rec	11
ECE	E4-106R-001392

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
50	870	1135	1395	1595	1860	2120	2265	2495	2730	2900
40	870	1135	1395	1595	1860	2120	2265	2495	2730	2900
30	975	1270	1560	1790	2080	2375	2535	2795	3055	3250
25	1040	1350	1660	1905	2215	2525	2695	2975	3250	3455
20	1100	1430	1755	2015	2340	2670	2855	3145	3440	3655
10	1220	1585	1950	2235	2600	2965	3170	3495	3820	4060

Printed on 27/04/2024 11:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..