

## AW 729 - Spécifications techniques



### Description

L'AW 729 est un pneu agricole spécialement conçu pour le transport, la récolte du foin, le bottelage et le travail des sols. Son épaulement arrondi et la conception de sa bande de roulement à trois rainures centrales assurent un faible compactage du sol et évitent les dégâts causés au champ. L'AW 729 est le pneu idéal pour l'agriculture moderne. Il est adapté pour une utilisation aussi bien sur route que hors route.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Presse à paille • Outillage agricole • Remorque

Version	STANDARD
Type	TL
Tyre Size	380/55 - 17
LI/SS DRIVE WHEEL	122 A8
LI/SS FREE ROLLING	134 A8

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	385
Overall Diameter (mm)	850
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2560
Rim Rec	13.00
Rim Alt	13 ; W 13
ECE	E11-106R-008727

## Load capacity (Kg)

km/h / bar	2.60
10 FR	2970
25 FR	2520
30 FR	2375
40 FR	2120
10 DW	2100
25 DW	1785
30 DW	1680
40 DW	1500

Printed on 20/04/2024 17:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..