

AW 729 - Spécifications techniques



Description

L'AW 729 est un pneu agricole spécialement conçu pour le transport, la récolte du foin, le bottelage et le travail des sols. Son épaulement arrondi et la conception de sa bande de roulement à trois rainures centrales assurent un faible compactage du sol et évitent les dégâts causés au champ. L'AW 729 est le pneu idéal pour l'agriculture moderne. Il est adapté pour une utilisation aussi bien sur route que hors route.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Outillage agricole • Remorque

| | |
|--------------------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 500/50 - 17 |
| LI/SS DRIVE WHEEL | 137 A8 |
| LI/SS FREE ROLLING | 149 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94067466 |
| Section Width (inch) | 19.7 |
| Overall Diameter (inch) | 37.2 |
| Static Loaded Radius (inch) | 16.8 |
| Rolling Circumference (inch) | 113.6 |
| Rim Rec | 16.00 |
| ECE | E11-106R-006616 |

Load capacity (lbs)

| mph / psi | 41 |
|-----------|-------|
| 5 FR | 10010 |
| 15 FR | 8510 |
| 20 FR | 8010 |
| 25 FR | 7150 |
| 5 DW | 7110 |
| 15 DW | 6045 |
| 20 DW | 5690 |
| 25 DW | 5080 |

Printed on 23/04/2024 11:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..