

AW 909 - Spécifications techniques



Description

AW 909 a été conçu pour le travail de la terre, le récolte du foin et les applications de transport avec outils agricoles, remorques et presses à paille. Ce pneu est idéal pour être utilisé dans l'agriculture moderne tant sur route que hors route.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Outillage agricole • Remorque

| | |
|--------------------|--------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 10.0/80 - 12 |
| LI/SS FREE ROLLING | 121 A8 |

Dimensions US Standard

| | |
|------------------------------|----------------|
| Usa code | 94010547 |
| Ply Rating | 10 |
| Section Width (inch) | 10.4 |
| Overall Diameter (inch) | 28 |
| Static Loaded Radius (inch) | 12.3 |
| Rolling Circumference (inch) | 81.9 |
| Rim Rec | 9.00 |
| Rim Alt | 7.0 |
| ECE | E4-106R-002662 |

Load capacity (lbs)

| mph / psi | 57 |
|-----------|------|
| 5 FR | 4480 |
| 15 FR | 3800 |
| 20 FR | 3580 |
| 25 FR | 3200 |

Printed on 24/04/2024 09:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..