



## BK 308 - Spécifications techniques



### Description

BK 308 a été particulièrement conçu pour les remorques et tracteurs compacts. Ce pneu se distingue de par une excellente traction sur toutes les surfaces et par des éléments intermédiaires (tie bar) entre les pavés de la bande de roulement pour limiter les fissures de contrainte dans cette dernière. La carcasse robuste réalisée avec un mélange spécial de la bande de roulement offre une excellente durabilité et une résistance exceptionnelle aux crevaisons, ce qui assure une plus longue vie du pneu.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Agriculture: Tracteur compact • Remorque

Version	STANDARD
Type	TT
Tyre Size	6.50 - 20
LI/SS	104 A8

## Dimensions US Standard

Usa code	94044993
Ply Rating	10
Section Width (inch)	7.5
Overall Diameter (inch)	34.1
Rim Rec	5.50 F
Rim Alt	4.00 E ; 5.00 F
ECE	E11-106R-003563

## Load capacity (lbs)

mph / psi	70
25	1985

Printed on 09/04/2024 22:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..