

BK 823 - Spécifications techniques



Description

BK 823 est un pneu essentiellement conçu pour les tracteurs, outils agricoles et remorques dans les applications de transport et travail de la terre. Le dessin spécial à blocs de sa bande de roulement fait qu'il est particulièrement adapté pour les opérations pénibles en offrant une excellente performance de direction. Une version HD, qui assure une résistance avancée aux coupures et déchirures, est aussi disponible.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Tracteur • Remorque

Version	STANDARD
Type	TT
Tyre Size	9.00 - 16
LI/SS	124 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	245
Overall Diameter (mm)	891
Static Loaded Radius (mm)	394
Rolling Circumference (mm)	2583
Rim Rec	6.5
ECE	E11-106R-003603

Load capacity (Kg)

km/h / bar	3.80
40	1600

Printed on 26/04/2024 10:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..