

BK 826 - Spécifications techniques



Description

BK 826 a été spécialement conçu pour les remorques dans les applications de transport. C'est un pneu diagonal caractérisé par une capacité de charge élevée grâce à la carcasse renforcée. BK 826 est disponible aussi en version industrielle « industrial » qui offre une résistance particulière aux coupures et il convient également pour les chargeuses-pelleteuses.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Remorque

Industriel: Chargeuse-pelleteuse • Remorque

Version	STANDARD
Type	TT
Tyre Size	9.00 - 16

Dimensions US Standard

Usa code	94026814
Ply Rating	12
Section Width (inch)	10.4
Overall Diameter (inch)	36.4
Rim Rec	6.50 H
Rim Alt	6.00 G

Load capacity (lbs)

mph / psi	75
20	4190

Printed on 26/04/2024 20:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..