

## COMMANDER 3 RIB - Fiche de données



### Description

COMMANDER 3 RIB est un pneu avant avec nervure de la bande de roulement à 3 côtes adapté pour les applications de travail de la terre et de transport. Il offre excellentes durabilité et capacité de charge, grâce à une répartition des poids optimisée sur les côtes dans la partie centrale et dans la zone de l'épaule. La carcasse robuste et le mélange résistant à tous les types de coupure assurent une excellente résistance aux crevaisons.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Tracteur 2WD

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	TMPH	ECE
6.00 - 16	STANDARD	94046911	F2	91 A8	8	4.50 E	4.00 E ; 5.00 F	6.9	29.1	TT	0	E11-106R-004415
6.50 - 16	STANDARD	94074501	F2	90 A8	8	4.50 E	4.00 E ; 5.00 F ; 5.50 F	7.2	30.1	TT	1	E11-106R-008288

Printed on 26/04/2024 09:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..