

COMMANDER (R) - Spécifications techniques



Description

COMMANDER (R) est un pneu agricole caractérisé par une bande de roulement profonde avec une base forte des pavés qui assure un cycle de vie plus long au pneu. Le dessin spécial des pavés à deux angles garantit tant une excellente traction aux champs que des propriétés élevées d'auto-nettoyage. La carcasse robuste est réalisée dans un mélange particulièrement résistant à tous les types de coupure qui confère aussi une grande capacité de charge.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Moissonneuse • Tracteur

Version	STANDARD
Type	TT
Tyre Size	9.5 - 36
LI/SS	126 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	246
Overall Diameter (mm)	1376
Rim Rec	W 8
Rim Alt	W 7
ECE	E11-106R-007809
TRA Code	R1

Load capacity (Kg)

km/h / bar	4.20
30	1700

Printed on 20/04/2024 12:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..