

## CON STAR - Spécifications techniques



### Description

CON STAR est particulièrement adapté pour les chargeuses compactes et chargeuses télescopiques dans les applications agro-industrielles de levage et de chargement. Ce pneu est caractérisé par une traction exceptionnelle associée à une excellente stabilité verticale et horizontale. CON STAR a été réalisé dans un mélange particulièrement résistant à tous les types de coupure qui contribue à allonger le cycle de vie du pneu.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique

Industriel: Chargeuse compacte • Chargeuse télescopique

Version	INDUSTRIAL
Type	TL
Tyre Size	400/70 - 24 (16.0/70 - 24)
LI/SS	158 A8

## Dimensions International Standard

Section Width (mm)	395
Overall Diameter (mm)	1175
Static Loaded Radius (mm)	544
Rolling Circumference (mm)	3556
SRI (mm)	575
Rim Rec	13
Rim Alt	DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L
ECE	E11-106R-003025

## Load capacity (Kg)

km/h / bar	5.00
40	4250

Printed on 20/04/2024 04:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..