

## CON STAR - Fiche de données



### Description

CON STAR est particulièrement adapté pour les chargeuses compactes et chargeuses télescopiques dans les applications agro-industrielles de levage et de chargement. Ce pneu est caractérisé par une traction exceptionnelle associée à une excellente stabilité verticale et horizontale. CON STAR a été réalisé dans un mélange particulièrement résistant à tous les types de coupure qui contribue à allonger le cycle de vie du pneu.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique

Industriel: Chargeuse compacte • Chargeuse télescopique

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
<b>340/80 - 18</b> <b>(12.5/80 - 18)</b>	INDUSTRIAL	143 A8		11	12 ; 11 SDC ; 12 SDC ; W 10 ; W 11	350	1015	465	3040	475	TL	E11-106R-003020
<b>340/80 - 20</b> <b>(12.5/80 - 20)</b>	INDUSTRIAL	144 A8		11	12 ; 11 SDC ; 12 SDC ; W 10 ; W 11	350	1065	491	3272	500	TL	E11-106R-003021
<b>380/75 - 20</b> <b>(14.5 - 20)</b>	INDUSTRIAL	148 A8		W 12	W 11 ; 12 SDC ; 12 ; W 13 ; 13 SDC ; 13	385	1080	500	3273		TL	E11-106R-003022
<b>400/70 - 20</b> <b>(16.0/70 - 20)</b>	INDUSTRIAL	149 A8	16	13	12 SDC ; 13 SDC ; 14	405	1080	501	3303	525	TL	E11-106R-003024
<b>400/70 - 20</b> <b>(16.0/70 - 20)</b>	INDUSTRIAL	156 A8		13	12 SDC ; 13 SDC ; 14	405	1080	501	3303	525	TL	E11-106R-003023
<b>400/70 - 24</b> <b>(16.0/70 - 24)</b>	INDUSTRIAL	158 A8		13	DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L	395	1175	544	3556	575	TL	E11-106R-003025
<b>400/80 - 24</b> <b>(15.5/80 - 24)</b>	INDUSTRIAL	162 A8	20	DW 13	DW 12 ; DW 13 L ; DW 14 L	405	1250	570	3781	600	TL	E11-106R-003026
<b>440/80 - 24</b> <b>(17.0/80 - 24)</b>	INDUSTRIAL	168 A8	22	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	455	1315	610	3986	625	TL	E11-106R-003027
<b>460/70 - 24</b> <b>(17.5L - 24)</b>	INDUSTRIAL	159 A8		DW 15 L	DW 14 L ; DW 16 L	460	1250	562	3784	600	TL	E11-106R-003029
<b>500/70 - 24</b> <b>(19.5L - 24)</b>	INDUSTRIAL	164 A8		DW 16 L	DW 15 L ; DW 18 L	505	1300	579	3926	625	TL	E11-106R-003031
<b>480/80 - 26</b> <b>(18.4 - 26)</b>	INDUSTRIAL	160 A8		DW 15 L	DW 16 L	490	1410	643	4272	675	TL	E11-106R-003033
<b>440/80 - 28</b> <b>(16.9 - 28)</b>	INDUSTRIAL	156 A8		DW 14 L	DW 13 ; DW 13 L ; DW 15 L	450	1420	632	4299	675	TL	E11-106R-003035

Printed on 20/04/2024 04:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..