

CONTAINER KING - Spécifications techniques



Description

CONTAINER KING a été conçu pour reach stackers dans les applications de transport et logistiques. Ce pneu extraordinaire a été réalisé avec un mélange de la bande de roulement extrêmement résistant à l'usure, ce qui réduit les fissures sur cette dernière. CONTAINER KING bénéficie d'un cycle de vie plus long et d'une stabilité optimale en mode levage.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Reach stacker

Version	INDUSTRIAL
Type	TT
Tyre Size	12.00 - 24

Dimensions US Standard

Usa code	94069798
Ply Rating	24
Overall Width (inch)	13
Overall Diameter (inch)	50.6
Rim Rec	8.5
Rim Alt	8.0
TRA Code	IND4

Load capacity (lbs)

mph / psi	145
5	22650

Printed on 20/04/2024 12:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..