

CRANE SPECIAL - Spécifications techniques



Description

CRANE SPECIAL est adapté pour les grues mobiles "pick & carry" sur les terrains accidentés. Ce pneu est réalisé dans un mélange spécial qui offre une stabilité et une durabilité élevées.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Grue automotrice

Version	STANDARD
Type	TL
Tyre Size	16.00 - 25

Dimensions US Standard

Usa code	94040582
Ply Rating	28
Overall Width (inch)	18.2
Overall Diameter (inch)	58.5
Static Loaded Radius (inch)	26.9
Rolling Circumference (inch)	173
Rim Rec	11.25/2.0
TRA Code	E3

Load capacity (lbs)

mph / psi	83
30	14800

Printed on 20/04/2024 12:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..