

DESERT KING - Spécifications techniques



Description

Le DESERT KING est le mieux adapté aux sols meubles, aux terrains sablonneux et aux finisseurs avec des « desert trucks ». La conception optimisée de la bande de roulement à nervures offre une flottaison et une stabilité directionnelle excellentes. Sa carcasse en nylon robuste et son talent très résistant sont spécialement conçus pour des conditions d'utilisation à basse pression. Le DESERT KING offre également une résistance élevée aux perforations et une durée de vie prolongée du pneu.

UM

US Standard

Construction

❖ BIAS

Machinery

OTR: Desert Truck

Version	STANDARD
Type	TL
Tyre Size	21.00 - 25 DT

Dimensions US Standard

Usa code	94067633
Ply Rating	16
Section Width (inch)	22.4
Overall Diameter (inch)	65.4
Static Loaded Radius (inch)	27.9
Rolling Circumference (inch)	193.1
Rim Rec	15.00/3.0
TRA Code	E7

Load capacity (lbs)

mph / psi	36
5	21500
30	14800
40	12300

Printed on 25/04/2024 16:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..