

# EARTHMAX SR 22 AS - Spécifications techniques



## Description

L'EARTHMAX SR 22 AS (E-2\*\*/G-2\*/L-2\*\*) est un pneu radial tout en acier spécialement conçu pour les niveleuses, les petites chargeuses et les camions pour la neige et la glace, mais qui assure des performances optimales toute l'année.

La conception unique de la bande de roulement, avec des lamelles profondes et un ensemble de quatre blocs, ainsi que les composés uniques pour l'hiver assurent un freinage optimal sur la glace ou la neige et évitent la rétention de cailloux, quelle que soit la période de l'année.

Le faible taux de vide et la large zone d'empreinte de l'EARTHMAX SR 22 AS offrent une traction et une stabilité exceptionnelles, avec une usure uniforme et une longue durée de vie de la bande de roulement.

## UM

International Standard

## Construction

 RADIAL

## Machinery

OTR: Niveleuse • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	14.00 R 24
LI/SS	153 A8/175 A2

## Dimensions International Standard

Overall Width (mm)	390
Overall Diameter (mm)	1370
Static Loaded Radius (mm)	625
Rolling Circumference (mm)	4141
Rim Rec	8.00 TG
Rim Alt	9.00 GR , 10.00 VA
Star Rating	*
TRA Code	G2/L2

## Load capacity (Kg)

km/h / bar	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	5.25	5.50
40	2240	2430	2650	2800	3000	3250	3350	3650	-	-
10	-	-	-	-	-	-	-	-	6700	6900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/12/2024 12:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..