

EARTHMAX SR 23 - Spécifications techniques



Description

EARTHMAX SR 23 (G-2/L-2) est un pneu radial All Steel (Tout Acier) particulièrement conçu pour les niveleuses et chargeuses. Il se distingue de par une excellente traction antérieure et latérale ainsi que par une capacité d'auto-nettoyage exceptionnelle. La carcasse robuste et la bande de roulement particulièrement résistante aux coupures lui assurent un long cycle de vie.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Niveleuse • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	15.5 R 25
LI/SS	146 A8/169 A2

Dimensions International Standard

Overall Width (mm)	383
Overall Diameter (mm)	1264
Static Loaded Radius (mm)	559
Rolling Circumference (mm)	3756
Rim Rec	12.00/1.3
Star Rating	*
TRA Code	G2/L2

Load capacity (Kg)

km/h / bar	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00	4.25	4.50	4.75	5.00
40	1550	1750	2000	2180	2360	2575	2800	3000	-	-	-	-	-
10	-	-	-	-	-	-	-	-	5000	5150	5450	5600	5800

Printed on 24/04/2024 19:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..