

EARTHMAX SR 30 - Spécifications techniques



Description

EARTHMAX SR 30 (E-3/L-3) est un pneu radial **All Steel** (Tout Acier) conçu pour une double utilisation avec chargeuses ou tombereaux rigides. Les ceintures d'acier multicouches et le dessin rigide à blocs assurent une traction, une stabilité et une durabilité excellentes. Le mélange spécial résistant aux coupures fait de EARTHMAX SR 30 la solution idéale pour un grand nombre de conditions opérationnelles difficiles.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Tombereau articulé • Bulldozer • Chargeur

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 15.5 R 25 |
| LI/SS | 160 B/169 A2 |

Dimensions International Standard

| | |
|----------------------------|-----------|
| TKPH | 130 |
| Overall Width (mm) | 397 |
| Overall Diameter (mm) | 1276 |
| Static Loaded Radius (mm) | 574 |
| Rolling Circumference (mm) | 3809 |
| Rim Rec | 12.00/1.3 |
| Rim Alt | - |
| Star Rating | **/* |
| TRA Code | E3/L3 |

Load capacity (Kg)

| km/h / bar | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 | 5.25 |
|------------|------|------|------|------|------|------|
| 50 | 3650 | 3875 | 4000 | 4250 | 4375 | 4500 |
| 10 | 5000 | 5150 | 5450 | 5600 | 5800 | - |

Printed on 15/04/2024 11:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..