

EARTHMAX SR 32 - Fiche de données



Description

EARTHMAX SR 32 est un pneu radial large non directionnel adapté pour les décapeuses. Ce pneu est caractérisé par une carcasse robuste All Steel et par un mélange spécial qui garantissent une résistance aux coupures et crevaisons ainsi que durabilité excellentes. Les autres avantages sont traction et flottaison extraordinaires même dans les conditions de service les plus sévères.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Décapeuse

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
29.5 R 29	CUT RESISTANT COMPOUND	94066216	E3	**	202 B	25.00/3.5	24.00/3.5	30.1	78	34.8	236.6	TL	197
33.25 R 29	CUT RESISTANT COMPOUND	94057986	E3	**	209 B	27.00/3.5	26.00/3.5	33.3	81.9	36	246.1	TL	237
37.25 R 35	CUT RESISTANT COMPOUND	94064243	E3	**	218 B	31.00/4.0		37.9	93.7	41.8	284.6	TL	310
40.5/75 R 39	CUT RESISTANT COMPOUND	94066506	E3	**	225 B	32.00/4.5		38.8	102.8	45.8	312	TL	346
40.5/75 R 39	STANDARD COMPOUND	94069392	E3	**	225 B	32.00/4.5		38.8	102.8	45.8	312	TL	472

Printed on 23/04/2024 11:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..