

# EARTHMAX SR 33 PLUS - Spécifications techniques



## Description

EARTHMAX SR 33 PLUS est un pneu radial avec un dessin particulier à blocs multiples conçu pour assurer une excellente traction sur les surfaces molles, sablonneuses ou boueuses. La carcasse All Steel robuste avec les ceintures d'acier se distinguent de par une excellente durabilité et une grande résistance aux coupures et crevaisons. EARTHMAX SR 33 PLUS offre une excellente stabilité ainsi que des propriétés d'auto-nettoyage exceptionnelles.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Industriel: Véhicule universel

Version	STANDARD
Type	TL
Tyre Size	16.00 R 20
LI/SS	173/170 G

## Dimensions US Standard

Usa code	94064038
Overall Width (inch)	17.6
Overall Diameter (inch)	51.6
Static Loaded Radius (inch)	22.9
Rolling Circumference (inch)	156.5
Rim Rec	11.25
Rim Alt	10.00W, 10.0
ECE	E11-54R-0017916

## Load capacity (lbs)

mph / psi	110
56	14330

Printed on 20/04/2024 12:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..