

EARTHMAX SR 331 - Spécifications techniques



Description

L'EARTHMAX SR 331 est le nouveau pneu à bande de roulement multi-blocs de BKT spécialement conçu pour les camions polyvalents et les véhicules d'intervention d'urgence. Le dessin unique de la bande de roulement est essentiel pour maximiser le contact avec le sol et garantit donc une excellente tenue de route et un confort optimal dans toutes les conditions. Ce pneu non directionnel possède des propriétés d'auto-nettoyage exceptionnelles. L'EARTHMAX SR 331 a été conçu par BKT pour offrir une flottaison et une traction excellentes, des exigences essentielles pour travailler efficacement sur des sols mous, sableux et boueux. La durée de vie étendue est assurée par l'ensemble carcasse et ceinture très robuste et tout en acier, qui offre également une résistance exceptionnelle aux déchirures et aux crevaisons.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Véhicule universel

Version	STANDARD
Type	TL
Tyre Size	24 R 21
LI/SS	176 G

Dimensions US Standard

Usa code	94067671
Ply Rating	16
Overall Width (inch)	23.9
Overall Diameter (inch)	54.4
Static Loaded Radius (inch)	24.7
Rolling Circumference (inch)	165.1
Rim Rec	18.00
ECE	E11-54R-0019350

Load capacity (lbs)

mph / psi	85
56	15700

Printed on 04/03/2024 11:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..