

EARTHMAX SR 34 - Spécifications techniques



Description

EARTHMAX SR 34 est un pneu radial All Steel (Tout Acier) spécialement conçu pour les tombereaux rigides dans différentes applications telles que les opérations dans les mines et carrières, dans les forêts, et le transport. Le dessin non directionnel de la bande de roulement assure d'excellentes traction et stabilité sur n'importe quel terrain. EARTHMAX SR 34 est idéal pour déplacer des charges lourdes. La carcasse All Steel robuste garantit une résistance optimale à l'usure et à tout type de crevaisons et déchirures. La tringle renforcée et le dessin particulier de l'épaule contribuent à assurer un plus long cycle de vie du pneu même dans les conditions de service les plus difficiles

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Tombereau rigide

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	16.00 R 25
LI/SS	177 B

Dimensions US Standard

Usa code	94070732
TMPH	130
Overall Width (inch)	17.3
Overall Diameter (inch)	59.4
Static Loaded Radius (inch)	27.3
Rolling Circumference (inch)	180.1
Rim Rec	11.25/2.0
Star Rating	**
TRA Code	E3+

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	12300	12800	13200	13900	14300	14800	15200	15700	16100

Printed on 03/05/2024 14:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..