

## EARTHMAX SR 34 - Fiche de données



### Description

EARTHMAX SR 34 est un pneu radial All Steel (Tout Acier) spécialement conçu pour les tombereaux rigides dans différentes applications telles que les opérations dans les mines et carrières, dans les forêts, et le transport. Le dessin non directionnel de la bande de roulement assure d'excellentes traction et stabilité sur n'importe quel terrain. EARTHMAX SR 34 est idéal pour déplacer des charges lourdes. La carcasse All Steel robuste garantit une résistance optimale à l'usure et à tout type de crevaisons et déchirures. La tringle renforcée et le dessin particulier de l'épaule contribuent à assurer un plus long cycle de vie du pneu même dans les conditions de service les plus difficiles.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Tombereau rigide

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
16.00 R 25	CUT RESISTANT COMPOUND	94070749	E3+	***	183 B	11.25/2.0		17.3	59.4	27.3	180.1	TL	130
16.00 R 25	CUT RESISTANT COMPOUND	94070732	E3+	**	177 B	11.25/2.0		17.3	59.4	27.3	180.1	TL	130

Printed on 03/05/2024 10:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..