

EARTHMAX SR 431 - Fiche de données



Description

EARTHMAX SR 431 (E-4) est un pneu radial All Steel particulièrement conçu pour les tombereaux rigides qui opèrent dans des conditions extrêmes, notamment dans les mines à ciel ouvert et souterraines. Le dessin non directionnel de la bande de roulement assure d'excellentes traction et stabilité. Ce pneu est caractérisé par une carcasse robuste All Steel et par un mélange spécial qui garantissent une résistance aux coupures et crevaisons ainsi que un cycle de vie plus long même dans les milieux rocheux, abrasifs et hostiles.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Tombereau rigide

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
16.00 R 25	CUT RESISTANT COMPOUND	E4	**	177 B	11.25/2.0		452	1532	713	4649	TL	166
18.00 R 25	CUT RESISTANT COMPOUND	E4	**	185 B	13.00/2.5		520	1660	760	5040	TL	140
18.00 R 25	CUT RESISTANT COMPOUND (UMS)	E4	****		13.00/2.5		520	1660	760	5040	TL	

Printed on 24/04/2024 04:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..