

EARTHMAX SR 43 - Spécifications techniques



Description

Earthmax SR 43 (L-4) est un pneu radial All Steel particulièrement conçu pour les chargeuses sur pneus qui opèrent dans des conditions rocheuses extrêmes, notamment dans les mines souterraines. Ce pneu garantit d'excellentes performances pour les opérations de chargement et de transport dans les mines à ciel ouvert, les carrières et les chantiers de démolition. Le dessin unique de la bande de roulement assure de meilleures traction et stabilité. Grâce à sa structure All Steel, Earthmax SR 43 (L-4) bénéficie d'une solidité optimale et d'une excellente résistance aux déchirures et crevaisons ainsi que d'un cycle de vie plus long.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	35/65 R 33
LI/SS	224 A2

Dimensions US Standard

Usa code	94067312
Overall Width (inch)	35.4
Overall Diameter (inch)	81.7
Static Loaded Radius (inch)	37.7
Rolling Circumference (inch)	252.4
Rim Rec	28.00/3.5
Star Rating	**
TRA Code	L4

Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	52000	55100	56800	58400	60000	61500

Printed on 20/04/2024 03:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..