

EARTHMAX SR 45 H2 - Spécifications techniques



Description

EARTHMAX SR 45 H2 est un pneu radial **All Steel** (Tout Acier) particulièrement conçu pour les tombereaux rigides. Le dessin unique de la bande de roulement d'une profondeur E-4 réduit l'usure ainsi que les bruits et vibrations. EARTHMAX SR 45 H2 est idéal pour toutes les opérations qui exigent traction et stabilité. Grâce à sa structure All Steel, le pneu bénéficie d'une excellente résistance aux déchirures et crevaisons ainsi que d'un cycle de vie plus long. Disponible avec mélange standard, résistant aux coupures ou à la chaleur.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Tombereau rigide

Version	HEAT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

Dimensions US Standard

Usa code	94060764
TMPH	298
Overall Width (inch)	26
Overall Diameter (inch)	85.8
Static Loaded Radius (inch)	38.5
Rolling Circumference (inch)	259.7
Rim Rec	17.00/3.5
Star Rating	**
TRA Code	E4

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	30900	32000	34200	35300	36400	37500	38600	39700	40800

Printed on 19/04/2024 19:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..